

TECHNICAL DATA SHEET


DAB12-110EV



ELECTRIC VEHICLE applications are wide and varied with many durability & power demands placed firmly on the batteries shoulders. OUR ELECTRIC VEHICLE AGM always delivers when you need it, whatever your DC requirement in general EV applications. Tough ABS case with INSERT TERMINALS as standard, smaller sizes with FASTON. Special Active Material Formulation & AGM Technology delivers cranking amps, general power and long/deep discharges. GOOD CYCLE LIFE and resistance to mechanical stress and the elements all in one battery.

	Dimensions mm - kg						Dimensions Inches - lbs						Cold Cranking Amps		
	Length	Width	Height Auto	Height Insert	Height Battery	Weight	Length	Width	Height Auto	Height Insert	Height Battery	Weight	20°C (68°F)	0°C (32°F)	-18°C (0°F)
DAB12-110EV	329	173	227	210	209	32.5	12.95	6.79	8.94	8.27	8.23	71.66	925	804	577

	Volts	Thread size mm	Reserve Capacity - Mins					Capacity - Ampere Hour*						
			75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr
DAB12-110EV	12	8	50	193	259	372	769	136	127	118	104.4	94.4	85.4	67.0



EV Charging - To obtain maximum cycle life from your EV battery it is important that a suitable charging profile is used. For information about the range of chargers and the recommended charging profile contact your local distributor.

NOTE : All our AGM batteries are true cycling batteries, plate chemistry is specifically for cyclic applications.